



Scope of supply: 2 carrying consoles (left and right side)
4 holders (premounted)

The carrying console is swivelling on the left and right side

Part no. for 1 pair	Max. load/pair (kN)	Length of support (L) (mm)	Dimensions (mm)								
			a ^{±0,2}	b ^{±0,1}	c ^{±0,1}	d	e	g	h	i	k ^{±0,1}
8.1835.1001	10	500	90	30	20	M16	Ø10	550	200	120	91,5
8.1835.1002	10	1000	90	30	70	M16	Ø10	1050	250	120	91,5
8.1835.1003	20	1000	90	30	120	M16	Ø10	1050	300	120	91,5
8.1835.1004	20	1250	90	30	170	M16	Ø10	1300	350	120	91,5
8.1835.1105	40	1000	90	30	210	M16	Ø10	1050	450	120	121,5
8.1835.1106	40	1250	90	30	260	M16	Ø10	1300	500	120	121,5
8.1835.1107	60	1000	90	30	310	M16	Ø10	1050	550	120	121,5
8.1835.1108	60	1250	90	30	460	M16	Ø10	1300	700	120	121,5

Carrying consoles are supplied in pairs with holders fastened, ready for connection
Special designs and double-swivel consoles are available on request.

**Special designs of carrying consoles,
e.g. sliding carrying consoles are available on request**

