

Supercraft mallet

non-rebound

Material:

Housing steel tube filled with steel bruised grain;
shaft steel tube with handle in corrugated rubber or
Hickory; mallet inserts in nylon, white (grease- and
oil-resistant)

Sample order:

nlm 96610-05002

Note:

Mallet Inserts for re-ordering see 96614.



Order No.	Surface finish	Head-Ø	Height	Length	Approx. weight g
96610-03001	shaft in Hickory	30	110	330	430
96610-04001	shaft in Hickory	40	115	360	750
96610-05001	shaft in Hickory	50	120	370	1000
96610-06001	shaft in Hickory	60	145	370	1700
96610-03002	shaft steel tube	30	110	290	580
96610-04002	shaft steel tube	40	115	300	850
96610-05002	shaft steel tube	50	120	310	1200
96610-06002	shaft steel tube	60	145	325	1780

Mallet inserts

for supercraft mallet

Material:

Nylon, white; grease- and oil-resistant

Sample order:

nlm 96614-04001



Order No.	for Head-Ø	Suitable for Supercraft soft hammers	Approx. weight g
96614-03001	30	96610-030..	23
96614-04001	40	96610-040..	39
96614-05001	50	96610-050..	51
96614-06001	60	96610-060..	106