

Klüber copper paste

lead-free



Sample order:
nlm 97903-400

Description:

The copper paste „Wolfracoat C“ is a metallic lubricating paste for use in temperatures up to 1200 °C.

Application:

Approved as an assembly, separating and lubricating paste for sliding contact bearings and lubricating points, roller bearings in foundries for cores and ejectors, in die-casting machines, exhaust systems of incinerator, power machine and coke oven plants.

Advantages:

The base oil evaporates at over 200 °C. A dry, metallic lubricant film gradually forms. Good lubrication of friction points with sliding and rolling friction, good separation and lubrication for stuck joints where there is friction at rest and in movement: improved sliding for easy assembly of interference and transition fits, easy dismantling when loosening stuck joints.

Order No.	Package	Working temperature	NLGI Class
97903-060	60 g tube	-30 °C up to 1200 °C, above 200 °C exchange into dry lubrication	2
97903-400	400 ml spray	-30 °C up to 1200 °C, above 200 °C exchange into dry lubrication	2

Klüber safety lubricating grease



Sample order:
nlm 97905-250

Description:

The safety lubricating grease „Microlube GL 261“ is a lubricant for high loads at low and high temperatures.

Application:

Lubricating grease for roller and sliding contact bearings, crown gears, steering racks, small gears, adjustment gears, winders and winches, roller guides, cams and cam plates.

Sealing and lubricating grease for oil and grease-resistant rubber seals such as radial packing rings, O-rings, cylinder and piston seals in the pneumatics industry; for rotary shaft lip seals (shaft seals), for plastics, sliding rails, sliding roofs and seat rails.

Anticorrosive grease for bright metal parts, locks, internal connection systems and ship fittings, for antennas, battery poles and to counter saltwater corrosion.

Advantages:

The MICROLUBE combination of active ingredients increases the percentage contact area of metal surfaces where there is micro-contact friction. The wear-free smooth coating (friction-point tempering) counteracts corrosion and fitting rust.

Order No.	Package	Working temperature	NLGI Class	Rev. characteristic n x dm
97905-250	250 ml spray	-30 °C up to 140 °C	1	3 x 100000
97905-400	400 g cartridge	-30 °C up to 140 °C	1	3 x 100000