

Klüber molybdenum disulphide lubricant



Sample order:
nlm 97907-1000

Description:

The molybdenum disulphide lubricant UNIMOLY GL 82 is a lubricating grease with MoS₂ for improved fail-safe procedures.

Application:

Approved for roller and slide bearings, sliding rails and guides, cams and cam plates, bolts, joints, hinges, cardan shafts, steering racks, threaded spindles across the entire machinery and mechanical engineering industry.

Approved for wheel bearing lubricant, as well as multipurpose lubricant for king pins, track rod joints, cardan shafts and spline shafts.

Advantages:

Contains molybdenum disulphide (MoS₂) for improved wear protection in the case of boundary lubrication; waterproof and corrosion preventive.

Based on automobile manufacturers' requirements.

Order No.	Package	Working temperature	NLGI Class	Rev. characteristic n x dm
97907-0400	400 g cartridge	-20 °C up to 130 °C	2	5 x 100000
97907-1000	1 kg can	-20 °C up to 130 °C	2	5 x 100000

Klüber liquid chain grease



Sample order:
nlm 97909-250

Description:

STRUCTOVIS BHD liquid chain grease is „chain honey“ for drive and control chains.

Application:

Approved for long-term lubrication for all drive and control chains. Especially also for water damp chains or open running toothed wheels and gearbox, on forklifts, conveyors, packaging machines, textile machines, robots, paper and wood processing machines.

Ideal for long-term lubrication of motorcycle chains. Is not washed off by rain or splashing water. Ideal for street racing, in particular for coupling chains, feeding mechanisms, crown gears. Protects and lubricates in sun, rain and snow.

Advantages:

Clings and sticks like honey. This „chain honey“ is colourless, transparent, creeps well, is wear and corrosion preventive, noise reducing and temperature resistant.

Order No.	Package	Working temperature	Kinematic viscosity DIN 51561 at 40 °C mm ² /s
97909-250	250 ml spray	-5 °C up to 120 °C	~4750